



UNIVERGE Desktop Digital Terminals

Fulfilling the promise of UNIVERGE®360

At a Glance

- Scalability and customization through modularity
- A full range of models and optional interfaces and modules
- Programmable line keys for immediate line/feature access or speed dialling
- Full duplex speaker (DT330)

UNIVERGE Desktop Digital Terminals offer features and benefits that brilliantly capture the essence of form and function while providing businesses the means to seamlessly communicate with their customers. These intelligent terminals help your business take service and performance to newer, more profitable heights.

Maximizing productivity

In today's intensely competitive business environment, smart companies know that it takes great customer service to get ahead.

Desktop Digital Terminals deliver exceptional value. With their user-friendly ergonomic design, a range of six models to choose from and a choice of interfaces and options, they provide users with access to the full power of UNIVERGE communication platforms.

Empowered by Innovation

NEC

Features		DT330	DT310
Display	Display size:	168x58 dot matrix B/W LCD Optional LCD backlit Optional 2nd display for DESI-less	6DE: 168x41 dot matrix B/W LCD, not backlit
	Characters × Lines:	Alphanumeric: 28x4 (6x12 font) DESI-less: 28x4 (6x12 font)	6DE: 24x3
	Tilttable:	Yes	N/A
Keypad	Backlit keypad:	Yes	N/A
	Line keys:	12, 24, 32 DESI-less: 8 x 4 pages	2, 6
	Softkeys:	4, help, exit	4, help, exit (only on 6DE)
	Cursor keys:	Yes	No
Built In Applications	Personal directory:	Yes	No
	System directory:	Yes	No
	Corporate directory:	Yes	No
	Call history:	Yes	No
Sound	Hands-free:	Full duplex	Yes
Optional Adapters	Recording Adapter:	Yes	N/A
	Analogue Port Adapter w/ringer:	Yes	N/A
	PSTN survivable adapter:	Yes	N/A
Other	Headset support	Yes	No
	Bluetooth hub	Yes	No
	Bluetooth handset	Yes	No
	Wall mountable capability	Yes	Yes
Characteristics	Dimension (w×d×h):	12D/24D: 179×258×112 mm 32D (24D+8LK): 205.8×258×112 mm DESI-less: 179×264×112 mm	2E: 179×225×112 mm 6DE: 179×225×112 mm
	Weight (approx. kgs.):	12D/24D: 1.2 kg 32D (24D+8LK): 1.3 kg DESI-less: 1.3 kg	2E: 1.0 kg 6DE: 1.1 kg
	AC adapter (option):	27V 750mA	27V 750mA
Standards	EMC:	The Desktop Digital Terminals carry a CE mark and comply with: EMC: EN55022 Emission EN55024 Immunity EN61000 Powering	
	RoHS:	All models comply with RoHS	
	Safety:	EN60950-1	
	UL/CSA:	FCC Part 15 Class B FCC Part 68	
	Transmission and signalling:	TBR8	
Environmentals	Operating conditions:	Temperature range: 0 to 40 °C, humidity: 10 to 90% RH (not condensing)	
	Storage:	Ambient temperature range: -20 to 60 °C, ambient humidity: 10 to 90 %RH	

UNIVERGE®360 is NEC's approach to unifying business communications. It places people at the center of communications and delivers on an organization's needs by uniting infrastructure, communications and business.



About NEC Corporation: NEC Corporation (NASDAQ: NIPNY) is one of the world's leading providers of Internet, broadband network and enterprise business solutions dedicated to meeting the specialized needs of its diverse and global base of customers. NEC delivers tailored solutions in the key fields of computer, networking and electron devices, by integrating its technical strengths in IT and Networks, and by providing advanced semiconductor solutions through NEC Electronics Corporation. The NEC Group employs more than 150,000 people worldwide. For additional information, please visit the NEC home page at: <http://www.nec.com>

For further information please contact your local NEC representative or:

EMEA (Europe, Middle East, Africa)
NEC Unified Solutions
www.nec-unified.com

North America (USA)
NEC Corporation of America
www.necam.com

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

Empowered by Innovation

